



INDUSTRIAL STUD MOUNTS



- 8mm Thread.
- Optimal Load Ranges 5 to 50 kg's.
- Colour Coded Parts to Differentiate Between Optimal Load Ranges.
- Excellent Dynamic Performance.
- All Parts Supplied With Nuts & Washers.

Used in a wide variety of applications to protect machinery from vibrations and impact in the medium-high frequency range (above 1000 rpm).

B Series					
Reference		Model	Colour	KG. Min ~ Max	Diameter
SE-BG-10	B		GREY	5 ~ 10	8mm
SE-BV-15			GREEN	10 ~ 20	
SE-BA-20			BLUE	20 ~ 30	
SE-BR-25			RED	30 ~ 50	

C Series					
Reference		Model	Colour	KG. Min ~ Max	Diameter
SE-CG-10	C		GREY	5 ~ 10	8mm
SE-CV-20			GREEN	10 ~ 20	
SE-CA-30			BLUE	20 ~ 30	
SE-CR-50			RED	30 ~ 50	

CR Series					
Reference		Model	Colour	KG. Min ~ Max	Diameter
SE-CRG-10	CR		GREY	5 ~ 10	8mm
SE-CRV-20			GREEN	10 ~ 20	
SE-CRA-30			BLUE	20 ~ 30	
SE-CRR-50			RED	30 ~ 50	

Gelmecc UK

Marcom House, 1-2 Steam Mill Lane, Great Yarmouth, Norfolk, NR31 0HP

Telephone: +44(0) 1493 668622 Fax: +44(0) 1493 668623

Email: sales@gelmecc.co.uk Website: www.gelmecc.co.uk